

How to install the National Safety Council safety tips widget on your intranet page

Typical intranet page left sidebar

Link
Link
Link
Link
Link
Link
Link
Link
Link
Link



Because we are a member of the National Safety Council, our employees get

SAFETY TIPS

from [Safety+Health magazine](#)

[FACEValue: Bulldozer operator, caught between track and fender, dies](#)

In February 2010, a 68-year-old construction site supervisor and heavy equipment operator with 48 years of experience died when ...

[Black ice: A hazard for drivers](#)


Black ice – which can be almost invisible – forms when the air temperature is warmer than pavement, which causes ...

[Emergency eye care](#)

Thousands of employees are blinded every year from work-related eye injuries, OSHA states.

[Match the pictogram to the hazard](#)

By Dec. 1, employers are required to have trained workers on chemical Safety Data Sheets and labels as part of OSHA's updated ...



100% of net column width of 200px. Height set at 400px.



Because we are a member of the National Safety Council, our employees get

SAFETY TIPS

from [Safety+Health magazine](#)

[FACEValue: Bulldozer operator, caught between track and fender, dies](#)

In February 2010, a 68-year-old construction site supervisor and heavy equipment operator with 48 years of experience died when ...

[Black ice: A hazard for drivers](#)

Black ice – which can be almost invisible – forms when the air temperature is warmer than pavement, which causes ...

[Emergency eye care](#)

Thousands of employees are blinded every year from work-related eye injuries, OSHA states.

[Match the pictogram to the hazard](#)

By Dec. 1, employers are required to have trained workers on chemical Safety Data Sheets and labels as part of OSHA's updated ...



100% of net column width of 170px. Height set at 450px.

Safety tips

NSC is excited to offer the 2014 Safety Tip Widget, a new safety resource available exclusively to our members. Use it to create a safety presence on your organizations intranet while you engage and educate your employees on issues affecting their safety and the safety of those around them.

As this is a member exclusive benefit, it is only available to members while their membership is in good standing. Each January the latest version will be released to all active members.

Instructions for placing the tips widget

Hand off these instructions to the people who maintain your intranet page. They will understand how to do this. The installation process is a one-time operation. The **Safety+Health** magazine staff will take care of updates on our end, and your employees will see links to fresh tips every month without further effort on your part.

Copy this code and paste it into the HTML source in the place on the page where you want the widget to appear.

The image is located on our server, so you don't have to worry about hosting it.

The copy-and-paste code will work for a widget of any width 300px or narrower. It will adjust to fit the width of the container (i.e., div or table cell) that you place it in, but you may need to adjust the height of the iframe. The iframe height attribute appears in the last section of the code:

```
<iframe src="http://www.safetyandhealthmagazine.com/ext/resources/files/topic-feeds/tipsfeed-snippet-no-top.htm" frameborder="0" scrolling="no" style="border:none; height:400px; width:100%;"></iframe>
```

The standard code is set for a widget height of 400 pixels. This should be the correct height for a container that is about 200px wide. If your container element is wider than 200px you will need to shorten the iframe height, and if it is narrower, you'll need a taller iframe. Experiment with it, especially if you will display other content beneath the widget and you don't want a vertical gap.

If your sidebar is about this wide:	Try setting the iframe height at:
170px	450px
200px	400px
300px	300px
More than 300px	Not recommended; the image will become distorted.



Because we are a member of the National Safety Council, our employees get

SAFETY TIPS

from [Safety+Health magazine](#)

[FACEValue: Bulldozer operator, caught between track and fender, dies](#)

In February 2010, a 68-year-old construction site supervisor and heavy equipment operator with 48 years of experience died when ...

[Black ice: A hazard for drivers](#)

Black ice – which can be almost invisible – forms when the air temperature is warmer than pavement, which causes ...

[Emergency eye care](#)

Thousands of employees are blinded every year from work-related eye injuries, OSHA states.

[Match the pictogram to the hazard](#)

By Dec. 1, employers are required to have trained workers on chemical Safety Data Sheets and labels as part of OSHA's updated ...



100% of net div width of 300px. Height set at 300px.